

INSTALLATION GUIDE ONLY

WOVEN WIRE FENCE

These instructions are provided as a guide only, if you need further advice, please contact Emu Wire Industries.

Generally the fence can be installed on a slope up to 12 degrees, anything greater will need to be stepped between posts.

A. Recommended Material Sizes

1. Strainer Post	EX 125mm x 125mm	(5" x 5")
2. Intermediate Posts	EX 125mm x 75mm	(5" x 3")
3. Top Rails	EX 100mm x 50mm	(4" x 2")
4. Plinth	EX 150mm x 38mm	(6" x 1.5")

B. Installation

1. Strainer Posts

Set into the ground 500mm to 600mm and strut well. Face of strainer posts should stand forward 25mm from face of top rail and should be level with gate posts.

2. Intermediate Posts

Maximum recommended spacing 2400mm and set back 25mm from strainer posts.

3. Top Rail

Let in flush with intermediate post and mortice into strainer post 25mm behind face of post. From ground to the top of the top rail should be 80mm less than the height of the woven wire, eg. For 1250mm wire it should be 1170mm to top of rail. The top two horizontal wires are to be evenly spaced and fixed to the top rail. If a different size top rail is used check the distance and ensure at least the top horizontal wire is fixed to the rail.

4. Plinth

Fixed flat on face of intermediate post and check into strainer posts to bring back of plinth flush with face of the top rail.

5. Wire

Place adjacent to strainer post prior to fixing and mark position of horizontal wires 25mm back from face. Drill 6mm hole and insert wire. Screw to secure. Staple top two wires to the face of the top rail. Staple bottom of wire to back of plinth and trim around intermediate posts.

